



Product Service

Attestation of Conformity

No. N8A 072092 0289 Rev. 03

Model(s):

Maximum System Voltage: 1000 V DC or 1500 V DC
 JAM72S01-xxx/PR, JAM72S04-xxx/PR, JAM72S06-xxx/PR,
 xxx=325 to 390 in step of 5;
 JAM60S01-xxx/PR, JAM60S04-xxx/PR, JAM60S06-xxx/PR,
 xxx=280 to 325 in step of 5;
 JAM72S01-xxx/SC, JAM72S04-xxx/SC, xxx =320 to 365 in step of 5;
 JAM60S01-xxx/SC, JAM60S04-xxx/SC, JAM60S06-xxx/SC,
 xxx=265 to 300 in step of 5; JAM72S03-xxx/PR, xxx=355 to 400 in step of 5;
 JAM60S03-xxx/PR, xxx = 295 to 335 in step of 5;
 JAM72S01-xxx/MR, xxx= 360 to 390 in step of 5;
 JAM60S01-xxx/MR, xxx= 300 to 330 in step of 5;
 Maximum System Voltage: 1500 V DC
 JAM6-72-xxx/SI/1500V, xxx =285 to 325 in step of 5;
 JAM6-60-xxx/SI/1500V, xxx =235 to 280 in step of 5;
 JAM6(R)-72-xxx/1500V, xxx =295 to 340 in step of 5;
 JAM6(R)-60-xxx/1500V, JAM6-60-xxx/4BB/1500V, xxx =255 to 280 in step of 5;
 JAM6-72-xxx/4BB/1500V, xxx =310 to 335 in step of 5;
 JAM6(L)-72-xxx/PR/1500V, xxx =325 to 345 in step of 5;
 JAM6(L)-60-xxx/PR/1500V, xxx =270 to 295 in step of 5;
 JAM6(K)-72-xxx/PR/1500V, xxx= 335 to 360 in step of 5;
 JAM6(K)-60-xxx/PR/1500V, xxx= 280 to 300 in step of 5;
 JAM6(K)-72-xxx/4BB/1500V, xxx =320 to 340 in step of 5;
 JAM6(K)-60-xxx/4BB /1500V, xxx =265 to 285 in step of 5;
 JAM72S09-xxx/PR, xxx= 370 to 390 in step of 5;
 JAM60S09-xxx/PR, xxx= 310 to 325 in step of 5;
 JAM72S10-xxx/PR, xxx= 380 to 415 in step of 5;
 JAM60S10-xxx/PR, xxx= 315 to 345 in step of 5;
 Maximum System Voltage: 1000 V DC
 JAM5(R)-72-xxx, JAM5(R)(BK)-72- xxx, xxx= 195 to 220 in step of 5;
 JAM5-72-xxx, JAM5(BK)-72-xxx, xxx= 155 to 195 in step of 5;
 JAM5(L)-72-xxx, JAM5(L)(BK)-72-xxx, xxx= 155 to 215 in step of 5;
 JAM5-72-xxx/SI, JAM5(BK)-72-xxx/SI, xxx= 180 to 210 in step of 5;
 JAM5(L)-72-xxx/SI, JAM5(L)(BK)-72-xxx/SI, xxx= 180 to 220 in step of 5;
 JAM5(L)-96-xxx, JAM5(L)(BK)-96-xxx, xxx= 210 to 260 in step of 5;
 JAM5(L)-96-xxx/SI, JAM5(L)(BK)-96-xxx/SI; xxx= 240 to 290 in step of 5;
 JAM6-72-xxx, JAM6(BK)-72-xxx, xxx= 255 to 305 in step of 5;
 JAM6-72-xxx/SI, JAM6(BK)-72-xxx/SI, JAM6(SE)-72-xxx/SI,
 xxx= 285 to 325 in step of 5;
 JAM6-60-xxx, JAM6(BK)-60-xxx, xxx= 200 to 250 in step of 5;
 JAM6-60-xxx/3BB, JAM6(BK)-60-xxx/3BB, xxx= 200 to 275 in step of 5;
 JAM6-60-xxx/SI, JAM6(BK)-60-xxx/SI, JAM6(SE)-60-xxx/SI,
 xxx= 235 to 280 in step of 5;
 JAM6-54-xxx, JAM6(BK)-54-xxx; xxx= 180 to 225 in step of 5;
 JAM6-54-xxx/3BB, JAM6(BK)-54-xxx/3BB; xxx= 180 to 250 in step of 5;
 JAM6-72-xxx/3BB, JAM6(BK)-72-xxx/3BB, xxx= 310 to 330 in step of 5;
 JAM6-54-xxx/SI, JAM6(BK)-54-xxx/SI, xxx= 225 to 240 in step of 5;
 JAM6(R)-54-xxx, JAM6(R)(BK)-54-xxx, xxx=230 to 250 in step of 5;
 JAM6(R)-48-xxx, JAM6(R)(BK)-48-xxx, xxx=205 to 225 in step of 5;
 JAM6-48-xxx/SI, JAM6(BK)-48-xxx/SI, xxx=200 to 220 in step of 5;
 JAM6(R)-72-xxx, JAM6(R)(BK)-72-xxx, xxx=295 to 340 in step of 5;
 JAM6(R)-60-xxx, JAM6(R)(BK)-60-xxx, JAM6(L)-60-xxx,
 JAM6(L)(BK)-60-xxx, JAM6-60-xxx/4BB, xxx=255 to 280 in step of 5;
 JAM6(L)-72-xxx, JAM6(L)(BK)-72-xxx, xxx=295 to 335 in step of 5;
 JAM6(TG)-60-xxx/SI, JAM6(BK)(TG)-60-xxx/SI, JAM6(BK)(SE)-60-xxx/SI,
 xxx=250 to 280 in step of 5;
 JAM6(FA)-60-xxx/SI, xxx=255 to 275 in step of 5;
 JAM6(FA)-48-xxx/SI, xxx=205 to 220 in step of 5;
 JAM6(R)(FA)-48-xxx, JAM6(K)-48-xxx/4BB, JAM6(K)(BK)-48-xxx/4BB,
 xxx= 210 to 225 in step of 5;

Page 2 of 4

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

ZERTIFIKAT • CERTIFICATE • 認證證書 • CERTIFICADO • CERTIFICAT

